

# 3M

# ScotchPad™

## Premium Hang Tabs

1072 • 1074 • 1075 • 1076

Technical Data

July, 2003

**Product Description** 3M™ ScotchPad™ Hang Tabs are designed to stick to a product surface and to then hang that product from a peg for display purposes.

The 3M™ ScotchPad™ Hang Tabs 1074, 1075 and 1076 are composed of a 3M™ Scotchpar™ polyester that is the most abrasion resistant backing with the most consistent pressure sensitive hot melt adhesive system available and is laminated to a thick polyester top in which a hole is punched for the peg. These precut tabs are prestacked 10 high in convenient pads for easy manual application and portability. They are handy for hanging shrink-wrapped packages as well as for in-store repair of damaged packaging. Because the whole tab is not rigid, the tab can be applied before case packing a product and will stay folded down until it is unpacked and hung up.

3M™ ScotchPad™ Hang Tab 1072 is composed of a clear, abrasion resistance co-polyester backing with a pressure sensitive hot melt adhesive system and an easy release coated paper liner. The single unit format J-hook tabs are designed for portability and manual application to shrink-wrapped packages as well as for in-store repair of damaged packaging.

<b>Construction</b>	Backing:	<b>ScotchPad hang tab 1072</b> <b>ScotchPad hang tabs 1074/1075/1076</b>	Co-polyester film Biaxially oriented 3M™ Scotchpar™ polyester film
	Adhesive:	<b>ScotchPad hang tab 1072</b> <b>ScotchPad hang tabs 1074/1075/1076</b>	Pressure sensitive rubber-resin adhesive Pressure sensitive hot melt rubber-resin adhesive
	Release Liner:	<b>ScotchPad hang tab 1072</b>	Blue paper, one side release coated
	Header Laminate:	<b>ScotchPad hang tabs 1074/1075/1076</b>	Copolyester PETG
	Holes:	<b>ScotchPad hang tabs 1074 and 1076</b> <b>ScotchPad hang tab 1075</b> <b>ScotchPad hang tab 1072</b>	Round – works with single pegs Delta – works with double pegs J-hook – works with single or double pegs

# 3M™ ScotchPad™

## Premium Hang Tabs

1072 • 1074 • 1075 • 1076

### Typical Physical Properties

**Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.**





3M™ ScotchPad™ Hang Tab 1072		ASTM Test Method
Adhesion to Steel:	175 oz./in. width (192 N/100 mm width)	PSTC-003
Tensile Strength:		
Machine Direction:	7300 lbs./in. <sup>2</sup> (513 kgf/cm <sup>2</sup> )	D-882
Tensile Modulus:		
Machine Direction:	250,000 lbs./in. <sup>2</sup> (17,575 kgf/cm <sup>2</sup> )	D-882
Elongation at Break:	300%	D-882
Thickness - Backing:	20.0 mil (0.508 mm)	D-3652
Total (excl. liner):	25.8 mil (0.655 mm)	D-3652
Shear, Static:	>30 hours (1.0 sq. in., 2.2 lb. @ 120°F [49°C])	PSTC-7C

3M™ ScotchPad™ Hang Tabs 1074/1075/1076		ASTM Test Method
Adhesion to Steel:	55 oz./in. width (60 N/100 mm width)	D-3330
Tensile Strength:		
Machine Direction:	45 lbs./in. width (788 N/100 mm width)	D-3759
Cross Direction:	65 lbs./in. width (1138 N/100 mm width)	D-3759
Elongation at Break:	130%	D-3759
Thickness Laminate:	10.0 mil (0.254 mm)	D-3652
Thickness - Backing:	2.0 mil (0.051 mm)	D-3652
Total:	3.5 mil (0.089 mm)	D-3652
Total Hang Tab (Top):	13.5 mil (0.343)	D-3652
Holding Power to Fiberboard:	12,000 + minutes	D-3654

### Features

- Adheres instantly to shrink-wrapped packages, cartons, and product surfaces.
- Strong abrasion, edge tear and split resistant backing.
- ScotchPad hang tabs 1074/1075/1076 have bendable tabs.
- Hold products out where they are easy to see.
- Strong film edge resists tearing and ripping of these hang tabs.
- Stiff polyester header gives clean product display.
- Clear tape does not obscure graphics.

### Available Sizes

			
J-hook ScotchPad hang tab 1072 1 pad	Round hole ScotchPad hang tab 1074 1 in. x 2 in. 10 per pad	Delta hole ScotchPad hang tab 1075 2 in. x 2 in. 10 per pad	Round hole ScotchPad hang tab 1076 2 in. x 2 in. 10 per pad

# 3M™ ScotchPad™

## Premium Hang Tabs

1072 • 1074 • 1075 • 1076

---

**Application Techniques** Application of 3M™ ScotchPad™ Hang Tabs is most easily accomplished at room temperature because at colder temperatures, approaching 32°F (0°C), the adhesive becomes firmer. Once applied, the ScotchPad hang tabs will perform well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments to a surface that allows a straight vertical position with no peel. Unless testing is done to confirm a ScotchPad hang tab will hold a heavier product, 3/4 lb. or less is the recommended weight unit. Some well-balanced three pound products have been displayed using two ScotchPad hang tabs placed on one object in opposing placement. Pre-testing is advised. Three ScotchPad 1074/1075/1076 hang tabs can be used to hold thick flat samples in a 3-ring binder. Because the whole tab is not rigid, they can also be pre-applied to products and folded down before shipping thus eliminating excessive shipping bulk. Some manufacturers pack extra pads in with product so the retailer can repair broken or damaged package chipboard headers thus reducing profit-stealing unsellables.

---

**Storage Conditions** Store in a clean dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended.

---

**For Additional Information** To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit [www.3M.com/packaging](http://www.3M.com/packaging). Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

---

**Product Use** All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

---

**Warranty and Limited Remedy** Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

---

**Limitation of Liability** Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



**Industrial Business  
Industrial Adhesives and Tapes Division**

3M Center, Building 21-1W-10, 900 Bush Avenue  
St. Paul, MN 55144-1000



*Recycled Paper*  
40% pre-consumer  
10% post-consumer

Printed in U.S.A.  
©3M 2003 70-0710-0247-4 (7/03)