



ScotchPad™

Pouch Tape Pads

830 • 832 • 830CP • 832CP

Technical Data

May, 2003

Product Description

3M™ ScotchPad™ Pouch Tape Pads are pre-cut pressure-sensitive tapes with a sticky border and a printed, non-tacky center section that comes either as a standard or custom printed pouch which is clear and becomes a “see-through” window. Each piece of tape is coupled with a strip of liner material for easy handling and application without the need of a dispenser. The product provides a quick, simple, and secure method of attaching and protecting packing lists and other documents on a wide range of shipping containers. With the liner left in place, the product may be used as an open-ended pouch, allowing work tickets, inventory lists, and other shipping documents to be inserted or removed as necessary.

Construction

Backing:	3M™ Scotchpro™ polypropylene film	
Adhesive:	Pressure-sensitive rubber resin	
Colors		
Standard Pouch Pad:	(830/832)	Transparent film with orange/white message border.
Custom-Printed Pouch Pad:	(830CP/832CP)	Transparent film with choice of two (2) colors and clear detackifying varnished center.
Dimensions		
Tape Sheet:	ScotchPad 830 – approximately 5 in. x 6 in. ScotchPad 832 – approximately 6 in. x 10 in.	
Tack Free Area:	ScotchPad 830 – approximately 4 in. x 4 ⁷ / ₈ in. ScotchPad 832 – approximately 5 in. x 8 ³ / ₄ in.	
Window (Readable Area):	ScotchPad 830 – approximately 3 ¹ / ₈ in. x 4 ¹ / ₂ in. ScotchPad 832 – approximately 4 in. x 7 ⁷ / ₈ in.	

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	50 oz./in. width (55 N/100 mm width)	D-3330
Tensile Strength:		
Crosswise:	30 lbs./in. width (525 N/100 mm width)	D-3759
Lengthwise:	60 lbs./in. width (1050 N/100 mm width)	D-3759
Total Thickness:	2.5 mil (0.066 mm)	D-3652
Elongation at Break:	160%	D-3759
Shear Holding to Fiberboard:	8000+ minutes	D-3654

Features

- Liner tab.
- Pre-cut individual sheets.
- Strong and abrasion-resistant.
- Easy removal of single sheets.
- Aggressive adhesive provides excellent adhesion to various surfaces.
- Easy removal of liner.
- Portable, lightweight.
- Space-saving.
- Standard and custom messages available.
- Consistent dimensions.

3M™ ScotchPad™

Pouch Tape Pads

830 • 832 • 830CP • 832CP

Features (continued)

- Exact replication of sheet size and border print.
- Helps prevent labels, invoices, and such from being scuffed off.
- Easy to read label.
- Holds securely to most cartons and containers; keeps packing list or label on package for safe delivery.
- Fast application; saves time.
- Easy to carry in pad form.
- Calls attention to and prevents disposal of documents.
- Excellent bar code protection.
- Customer's name, address, and logo or telephone and advertisement may be printed on the custom pouch tape pads.

Available Packaging

	Sheets/Pad	Pad/Carton	Cartons/Case	Pads/Case	Application/Case
3M™ ScotchPad™ 830	25	40	5	200	5000
3M™ ScotchPad™ 832	25	40	4	160	4000

Storage Conditions

It is recommended that 3M™ ScotchPad™ Pouch Tape Pads be stored below 85°F (29°C).

For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/packaging. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Important Notice

3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.

Limitation of Remedies and Liability

If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



Industrial Business
Industrial Adhesives and Tapes Division
 3M Center, Building 21-1W-10, 900 Bush Avenue
 St. Paul, MN 55144-1000



Recycled Paper
 40% pre-consumer
 10% post-consumer

Printed in U.S.A.
 ©3M 2003 70-0710-0270-6 (5/03)